

XL Grapple

SWEDISH QUALITY AT LOW PRICES

XL Grapple is designed and manufactured in Sweden, using Swedish steel. The grapples are available in a total of eight different variants: four standard grapples and four energy wood grapples.

XL Grapple
028

XL GRAPPLE STANDARD



Available in sizes suitable for both thinning and clear cutting. The grapple provides you with control over log handling and ensures smooth timber rolling while at the same time minimizing risk of the grapple digging into the ground.

Available in variants 025, 028, 035 and 040.

XL GRAPPLE ENERGY



Designed for efficient handling of brushwood and other bio material. The open, knifeless claws provide a strong grip on the material while easily releasing it when the grapple is opened.

Available in variants 025, 028, 035 and 040.

OPTIMIZED WEIGHT - LONG LIFESPAN - WEAR AND IMPACT RESISTANT

PRODUCT SPECIFICATIONS

XL GRAPPLE STANDARD



MODEL	025 STD	028 STD	035 STD	040 STD
Length, closed grapple	800 mm*	833 mm	875 mm	944 mm*
Width, outer grapple	394 mm*	394 mm	440 mm	440 mm*
Height, closed grapple	534 mm*	524 mm	566 mm	600 mm*
Height, open grapple	790 mm*	734 mm	698 mm	712 mm*
Max. grip width	1390 mm*	1497 mm	1758 mm	1954 mm*
Min. grapple diameter	100 mm*	100 mm	122 mm	136 mm*
Max. width	452 mm*	452 mm	490 mm	490 mm*
Point force, tip to tip	17 kN*	16,7 kN	16,2 kN	15,9 kN*
Max. working pressure	23 Mpa*	23 MPa	23 MPa	23 Mpa*
Opening time at 70 l/min	0,9 s*	1,0 s	1,1 s	1,2 s*
Closing time at 70 l/min	1,4 s*	1,5 s	1,6 s	1,7 s*
Max. load	3500 kg*	3500 kg	5000 kg	5000 kg*
Weight	175 kg*	187 kg	222 kg	240 kg*

XL GRAPPLE ENERGY



MODEL	025 ENERGY	028 ENERGY	035 ENERGY	040 ENERGY
Length, closed grapple	800 mm*	833 mm	874 mm	944 mm*
Width, outer grapple	418 mm*	418 mm	464 mm	464 mm*
Height, closed grapple	534 mm*	533 mm	578 mm	600 mm*
Height, open grapple	790 mm*	682 mm	637 mm	680 mm*
Max. grip width	1390 mm*	1510 mm	1753 mm	1950 mm*
Min. grapple diameter	100 mm*	115 mm	122 mm	136 mm*
Max. width	452 mm*	452 mm	490 mm	490 mm*
Point force, tip to tip	17 kN*	16,7 kN	16,2 kN	15,9 kN*
Max. working pressure	23 Mpa*	23 MPa	23 MPa	23 Mpa*
Opening time at 70 l/min	0,9 s*	1,0 s	1,1 s	1,2 s*
Closing time at 70 l/min	1,4 s*	1,5 s	1,6 s	1,7 s*
Max. load	3500 kg*	3500 kg	5000 kg	5000 kg*
Weight	181 kg*	195 kg	235 kg	257 kg*

* calculated data

WANT MORE INFO?

READ MORE

koppommaskin.com/xl-grapple

CONTACT US

+46 (0)571 210 00

info@koppommaskin.com



Koppom Maskin

Hålvägen 1
673 32 Charlottenberg